

# Digital Clocks

## 2.3"HM Digital Clock

**Product ID:CN01NF2HM**



**Enclosure type** : SS304  
**Display Format** : HH:MM  
**Product Dimensions** : 28.5 x 10.5 x 3.5cm  
(l \* w \* h)

## 2.3"HMS Digital Clock

**Product ID:CN01NF2HMS**



**Enclosure type** : SS304  
**Display Format** : HH:MM :SS  
**Product Dimensions** : 35.8 x 10.4 x 5 cm  
(l \* w \* h)

## 4"HM Digital Clock

**Product ID:CN01NF4HM**



**Enclosure type** : SS304  
**Display Format** : HH:MM  
**Product Dimensions** : 42.5 x 15.5 x 5 cm  
(l \* w \* h)

## 4"HMS Flameproof Digital Clock with SS enclosure

Product ID:CN01FS4HMS



**Enclosure type** :Aluminum Die Casting  
with SS 304 Cover

**Display Format** :HH:MM :SS

**Product Dimensions:**60 x 25 x 10cm(l\*w\*h)

## 4"HM Flameproof Digital Clock with SS enclosure

Product ID:CN01FS4HM



**Enclosure type** :Aluminum Die Casting  
with SS 304 Cover

**Display Format** :HH:MM

**Product Dimensions** :53 x 22.5 x 8c(l\*w\*h)

## 4"HM Flameproof Digital Clock

Product ID:CN01F4HM



**Enclosure type** : Aluminum Die Casting

**Display Format** : HH:MM

**Product Dimensions** : 53 x 22.5 x 8c(l\*w\*h)

DIGITAL SYNCHRONIZED CLOCK is the perfect solution for wide range of applications where accurate synchronized time is required for better operations in process industries.

The following are the main application areas where synchronized digital clocks play an important role.

- Pharmaceutical industries
- Warehouse
- Mass Production Factories
- Collages

## Applications:

- industries
- Warehouse
- Mass Production Factories

## Specifications & Features :

Time Synchronization with GPS time,24 Hours' Time Format, Updates the time using internal RTC in case of GPS failure.

- **General Specifications:**

- Display color - Super bright Red,
- Visibility - 100 feet,
- Display format - 24 hours.

- **RF Specifications:**

- TX Power - 25mW ,
- Signal input - RF SIGNAL 865 MHZ ,
- Signal output - RF SIGNAL 865 MHZ ,
- Antenna gain - 2dBi Omni Directional ,
- Line of Sight - 1Km.

- **Electrical Specifications:**

- Supply voltage - 230 volts AC ,
- Power Consumption - <10watt

**Contact**

CYBERNETICS

Hyderabad

PH: 040-48505525

MOBILE:9989822468

Mail: [info@cyberneticservices.in](mailto:info@cyberneticservices.in)